Spooky Rookies

Wonderwalls.01 Product Specification



Published: February 2020

Wonderwalls.01

Fitted with a wealth of play functions in a reduced space Wonderwalls are specifically aimed at the needs of toddlers and pre-school children. Each equipment design offers a number of play worlds that are interconnected by windows and passages between the three or respectively four walls, which are fanned out around a central post. As well as space for retreat, children are encouraged to engage in role-playing games using elements such as mud tables, benches, sand workshops or openings in the walls. Language and social skills are fostered and trained in a playful way.

The highlight of Wonderwalls.01 in the design of a tree stump is a passage with rubber membranes connecting two play areas. And anyone looking closely will find a secret opening under the bench.




Wonderwalls.01

90.295.700.1

90	.295./00.1	
(† 1997)	Product Family	Spooky Rookies
	Length x Width x Height (m) Length x Width x Height ('-'')	2,3 x 2,7 x 1,6 7-7 x 8-11 x 5-0
	Protective Surfacing Area acc. to DIN EN 1176 (m) Protective Surfacing Area acc. to ASTM/CSA (m) Protective Surfacing Area acc. to ASTM/CSA('-")	5,3 x 5,7 6,0 x 6,4 19-7 x 20-11
000↓	Fall Height acc. to EN 1176 (m) Fall Height acc. to ASTM/CSA ('-'')	0,94 4-10
$\stackrel{\circ}{\sqcap}\stackrel{\circ}{\sqcap}$	Age	2-5
	Minimum Space required acc. to DIN EN 1176 (ft^2) Minimum Space required acc. to ASTM 1487 (ft^2)	20.95 287.8
$\Diamond^{\diamondsuit} \Diamond$	Number of Foundations	5
	Concrete Volume C20/C25 (ft ³)	22.3
	Number of skilled Installers required	2
	Installation Time without Foundation	8 hours
	Dimensions of largest Part ('-'')	4-11 x 3-11
	Weight of heaviest Part (lbs)	88.2
	Shipping Volume (ft ³)	On request
îîî	Total Weight (lbs)	On request
\bigcirc	Spare Part Guarantee	Lifelong







Technical Data

The following text can also be used for tenders.

Included Products:

- Rubber Membrane Curtain
- Puzzle Elements
- Mud Tables
- Rotating Disc

Tubes:

The Steel tubes with a diameter of Ø 2 $\frac{3}{4}$ " and a wall thickness of $\frac{1}{6}$ " are thermally galvanized to protect against corrosion and powder-coated in color using a solvent-free epoxy/polyester/process. They are also watertight closed with rounded aluminum caps.

Panels:

Wall, play and design elements are made of solid-colored and grained HDPE panels with a thickness of $\frac{3}{4}$ and form milled. All edges are rounded off and the walls are connected to the pipes with cast aluminum panel clamps.

Rubber Membrane:

The rubber mat strips are made of durable and vandal-proof conveyor belt.